

DOUBLE ROW ANGULAR CONTACT BALL BEARINGS MAXIMUM TYPE							LOAD RATINGS (Lbs.)		
BEARING NUMBER	BORE d		OUTER DIAMETER D		WIDTH B		DYN	STATIC	BRG. WGT.
	mm	in.	mm	in.	mm	in.	Cr	Cor	
3302	15	.5906	42	1.6535	19	.7480	2890	2400	.280
3303	17	.6693	47	1.8504	22.2	.8740	3550	3050	.408
3304	20	.7874	52	2.0472	22.2	.8740	4300	3750	.487
3305	25	.9843	62	2.4409	25.4	1.0000	6000	5400	.780
3306	30	1.1811	72	2.8346	30.2	1.1890	7900	7350	1.23
3307	35	1.3780	80	3.1496	34.9	1.3740	10100	9600	1.67
3308	40	1.5748	90	3.5433	36.5	1.4370	11100	11300	2.27
3309	45	1.7717	100	3.9370	39.7	1.5630	13800	14300	3.02
3310	50	1.9685	110	4.3307	44.4	1.7480	16600	17700	4.37
3311	55	2.1654	120	4.7244	49.2	1.9370	19800	21400	5.34
3312	60	2.3622	130	5.1181	54	2.1260	23100	25400	6.77
3313	65	2.5591	140	5.5118	58.7	2.3110	26700	29900	8.60
3314	70	2.7559	150	5.9055	63.5	2.5000	31000	34000	11.5
3315	75	2.9528	160	6.2992	68.3	2.6890	35000	38500	13.9



**Pacific International  
Bearing, Inc.**

800.228.8895 • [www.pibsales.com](http://www.pibsales.com)