

BORE DIAMETER	BORE TOLERANCE	NOMINAL	PRESSFIT	O.D. TOLERANCE (1)		OUT OF ROUND (2)	
		METAL O.D.	RUBBER O.D.	METAL O.D.	RUBBER O.D.	METAL O.D.	RUBBER O.D.
Up to 1,000	+/- 0.001	+ 0.004	+ 0.006	+/- 0.002	+/- 0.003	0.005	0.010
1,001-2,000	+/- 0.001	+ 0.004	+ 0.006	+/- 0.002	+/- 0.003	0.006	0.012
2,001-3,000	+/- 0.001	+ 0.004	+ 0.006	+/- 0.002	+/- 0.003	0.007	0.014
3,001-4,000	+/- 0.0015	+ 0.005	+ 0.006	+/- 0.002	+/- 0.004	0.009	0.018
4,001-6,000	+/- 0.0015	+ 0.005	+ 0.010	+ 0.003 - 0.002	+/- 0.004	0.012	0.023
6,001-8,000	+/- 0.002	+ 0.006		+ 0.003 - 0.002		0.015	
8,001-9,000	+/- 0.002	+ 0.007		+ 0.004 - 0.002		0.015	
9,001-10,000	+/- 0.002	+ 0.008		+ 0.004 - 0.002		0.015	

BORE DIAMETER	BORE TOLERANCE	NOMINAL	PRESSFIT	O.D. TOLERANCE (1)		OUT OF ROUND (2)	
		METAL O.D.	RUBBER O.D.	METAL O.D.	RUBBER O.D.	METAL O.D.	RUBBER O.D.
Up to 25.00	+/- 0.025	+ 0.10	+/- 0.15	+/- 0.005	+/- 0.008	0.13	0.25
25.0-50.00	+/- 0.025	+ 0.10	+/- 0.15	+/- 0.005	+/- 0.008	0.15	0.30
50.01-75.00	+/- 0.025	+ 0.10	+/- 0.15	+/- 0.005	+/- 0.008	0.15	0.36
75.01-100.00	+/- 0.038	+ 0.13	+/- 0.20	+/- 0.005	+/- 0.10	0.18	0.46
100.01-150.00	+/- 0.038	+ 0.13	+/- 0.20	+ 0.08 - 0.05	+/- 0.10	0.23	0.58
150.01-200.00	+/- 0.0051	+ 0.15		+ 0.08 - 0.05		0.30	
200.01-225.00	+/- 0.0051	+ 0.18		+ 0.10 - 0.05		0.38	
225.01-250.00	+/- 0.0051	+ 0.20		+ 0.10 - 0.05		0.38	